

## A7/V7-EGP2

### A7/V7 Option Switch Settings : 1(Pulse/MDB)

**Supported bill EGP 5, 10 2bills.**

A7/V7 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★ Reject EGP 5	ON											
★ Accept EGP 5	OFF											
★ Reject EGP 10		ON										
★ Accept EGP 10		OFF										
★ Reserved			ON									
★ Reserved			OFF									
★ Reserved				ON								
★ Reserved				OFF								
★ Reserved					ON							
★ Reserved					OFF							
★ Reserved						ON						
★ Reserved						OFF						
★ Harness disable							ON					
★ Harness enable							OFF					
★ Inhibit Active High								ON				
★ Inhibit Active Low								OFF				
★ 1 pulse / EGP 5									OFF	OFF		
2 pulses / EGP 5									ON	OFF		
5 pulses / EGP 5									OFF	ON		
20 pulses / EGP 5									ON	ON		
★ Pulse Speed		50ms on / 50ms off									OFF	OFF
		60ms on / 300ms off									ON	OFF
		30ms on / 50ms off									OFF	ON
		150ms on / 150ms off									ON	ON

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

## A7/V7-EGP2(Pulse/MDB)

### Interface Settings: 2(Pulse)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Mode		ON		
MDB Interface		OFF		
★ Reserved			ON	
★ Reserved			OFF	
★ Reserved				ON
★ Reserved				OFF

★ Manufacture setting

### Interface Settings: 2(MDB)

INTERFACE	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
Pulse Interface		ON		
★ MDB Interface (Note)		OFF		
★ Reserved			ON	
★ Reserved			OFF	
★ Reserved				ON
★ Reserved				OFF

★ Manufacture setting

Note: Please refer to the dip-switch #1 of internal dip-switch for MDB Decimal Point Setup.

### Currency Assign Data

Interface Bill value	MDB	Pulse
BV1	EGP 5	EGP 5
BV2	EGP 10	EGP 10