

## V7E/LX7-EGP2

### V7E/LX7 Option Switch Settings: 1(Pulse/ICT104U/RS232 A0/ccNet)

**Supported bill EGP 5, 10 2 bills.**

V7E/LX7 dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject EGP 5	ON											
	Accept EGP 5	OFF											
	Reject EGP 10		ON										
★	Accept EGP 10		OFF										
	Reserved			ON									
★	Reserved			OFF									
	Reserved				ON								
★	Reserved				OFF								
	Reserved					ON							
★	Reserved					OFF							
	Reserved						ON						
★	Reserved						OFF						
	Reserved							ON					
★	Reserved							OFF					
	Harness Disable								ON				
★	Harness Enable								OFF				
	Inhibit Active High									ON			
★	Inhibit Active Low									OFF			
★	1 pulse / EGP 5									OFF	OFF		
	2 pulses / EGP 5									ON	OFF		
	5 pulses / EGP 5									OFF	ON		
	20 pulses / EGP 5									ON	ON		
★	Pulse Speed	50ms on / 50ms off									OFF	OFF	
		60ms on / 300ms off									ON	OFF	
		30ms on / 50ms off									OFF	ON	
		150ms on / 150ms off									ON	ON	

★ Manufacture setting

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

## V7E/LX7-EGP2(Pulse/ICT104U/RS232 A0/ccNet)

### DIP SWITCHES SETTING: 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON	OFF	
	ICT104U Mode		OFF	OFF	
	ccNet Mode		ON	ON	
	RS232 A0 Mode		OFF	ON	
	Reserved				ON
★					OFF

### DIP SWITCHES SETTING: 2(ICT)

	FUNCTION	SW1	SW2	SW3	SW4
	Reserved	ON			
★		OFF			
	Pulse Mode		ON	OFF	
★	ICT104U Mode		OFF	OFF	
	ccNet Mode		ON	ON	
	RS232 A0 Mode		OFF	ON	
	Reserved				ON
★					OFF

### DIP SWITCHES SETTING: 2(ccNet)

	FUNCTION	SW1	SW2	SW3	SW4
	Reserved	ON			
★	9600 Baud rate	OFF			
	Pulse Mode		ON	OFF	
	ICT104U Mode		OFF	OFF	
★	ccNet Mode		ON	ON	
	RS232 A0 Mode		OFF	ON	
	Reserved				ON
★					OFF

★ Manufacture setting

## Currency Assign Data

Interface Bill value	Pulse	RS232 A0	ccNet	ICT104U
BV1	EGP 5	EGP 5	EGP 5	EGP 5
BV2	EGP 10	EGP 10	EGP 10	EGP 10

### DIP SWITCHES SETTING: 2(RS232 A0)

	FUNCTION	SW1	SW2	SW3	SW4
	Reserved	ON			
★		OFF			
	Pulse Mode		ON	OFF	
	ICT104U Mode		OFF	OFF	
	ccNet Mode		ON	ON	
★	RS232 A0 Mode		OFF	ON	
	Reserved				ON
★					OFF

★ Manufacture setting

**Note:**

ESCROW DATA		CURRENCY ASSIGN DATA			
Code	Denomination	Code	Country	Denomination	Exp.
61h	Reserved	61h	00h	00h	00h
62h	EGP 5	62h	9Bh	05h	00h
63h	EGP 10	63h	9Bh	0Ah	00h
64h	Reserved	64h	00h	00h	00h
65h	Reserved	65h	00h	00h	00h
66h	Reserved	66h	00h	00h	00h
67h	Reserved	67h	00h	00h	00h
68h	Reserved	68h	00h	00h	00h