

V7E/LX7-TWD4

V7E/LX7 Option Switch Settings: 1(Pulse/ICT104U/MDB/RS232 A0)

Supported bill TWD 100, 200, 500, 1000 4 bills.

V7E/LX7 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★ Reject TWD 100	ON											
★ Accept TWD 100	OFF											
★ Reject TWD 200		ON										
★ Accept TWD 200		OFF										
★ Reject TWD 500			ON									
★ Accept TWD 500			OFF									
★ Reject TWD 1000				ON								
★ Accept TWD 1000				OFF								
★ Reserved					ON							
★ Reserved					OFF							
★ Reserved						ON						
★ Reserved						OFF						
Pulse Mode	Other Mode											
★ Harness Disable	BA stops working when fishing						ON					
★ Harness Enable	Normal						OFF					
★ Inhibit Active High							ON					
★ Inhibit Active Low							OFF					
★ 1 pulse / TWD 100							OFF	OFF				
★ 2 pulses / TWD 100							ON	OFF				
★ 10 pulses / TWD 100							OFF	ON				
★ 20 pulses / TWD 100							ON	ON				
★ Pulse Speed	50ms LO / 50ms HI								OFF	OFF		
	60ms LO / 300ms HI								ON	OFF		
	30ms LO / 50ms HI								OFF	ON		
	150ms LO / 150ms HI								ON	ON		

★ Manufacture setting

Note : (1) Default setting.

(2) Use 2nd and 3rd dip of the internal dip-switch to change different interface protocol.

(3) Remove the front cover and the dip-switch in on the CPU board.

(Please refer to "SW1" setting.)

Appendix

V7E/LX7-TWD4(Pulse/ICT104U/MDB/RS232 A0)

DIP SWITCHES SETTING: 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Mode		ON	OFF	
★ ICT104U Interface		OFF	ON	
MDB Interface		ON	ON	
RS232 A0 Mode		OFF	OFF	
★ Reserved				ON
				OFF

DIP SWITCHES SETTING: 2(ICT)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
	OFF			
★ Pulse Mode		ON	OFF	
★ ICT104U Interface		OFF	ON	
MDB Interface		ON	ON	
RS232 A0 Mode		OFF	OFF	
★ Reserved				ON
				OFF

DIP SWITCHES SETTING : 2(MDB) Currency Assign Data

FUNCTION	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
Pulse Mode		ON	OFF	
★ ICT104U Interface		OFF	ON	
MDB Interface		ON	ON	
RS232 A0 Mode		OFF	OFF	
★ Reserved				ON
				OFF

★ Manufacture setting

Interface Bill value	Pulse	RS232 A0	ICT104U	MDB
BV1	TWD 100	TWD 100	TWD 100	TWD 100
BV2	TWD 200	TWD 200	TWD 200	TWD 200
BV3	TWD 500	TWD 500	TWD 500	TWD 500
BV4	TWD 1000	TWD 1000	TWD 1000	TWD 1000

DIP SWITCHES SETTING: 2(RS232 A0)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
★ Reserved	OFF			
Pulse Mode		ON	OFF	
★ ICT104U Interface		OFF	ON	
MDB Interface		ON	ON	
★ RS232 A0 Mode		OFF	OFF	
★ Reserved				ON
				OFF

RS232 A0 INFORMATION

BillType Data	
Code	Denomination
1	Reserved
2	Reserved
3	Reserved
4	TWD 100
5	TWD 200
6	TWD 500
7	TWD 1000