

BR2300-JPY4

BR2300 DIP SWITCHES SETTING : (MDB/ICT-BC/ccTalk)

Supported bill JPY 1000, 2000, 5000, 10000 4 bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
	Reject JPY 1000 & 2000	ON									
★	Accept JPY 1000 & 2000	OFF									
	Reject JPY 5000 & 10000		ON								
★	Accept JPY 5000 & 10000		OFF								
	Accept only new JPY(2024)			ON							
★	Accept all JPY			OFF							
	High Acceptance (Note.3)				ON						
★	High Security				OFF						
★	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	(MDB Only)				ON					
	Credit divide by 1000 (Note.5)	(MDB Only)				OFF					
★	Normal					OFF	OFF				
	Load Banknote to Recycle					ON	OFF				
	Load Banknote to Stacker					OFF	ON				
	Unload Banknote to Stacker					ON	ON				
★	ccTalk							ON	OFF		
	ccTalk (Note.1)							OFF	ON		
★	MDB Mode							OFF	OFF		
★	ICT-BC Mode							ON	ON		
	ccTalk	MDB Mode				ICT-BC Mode					
★	Encryption MODE	Virtual MDB Recycler Function (Note.2)				Connect with MDB Connector					ON
	Decrypt MODE	Standard MDB Recycler Function				Connect with RS232 Connector					OFF

★ Manufacture setting

Note.1: Turn this dip to with restart the bill acceptor will restore ccTalk address to its default value of 40 and the encryption key to its default value of 123456.

Note.2: Recycled Banknote represents virtual MDB coin type.

Note.3: High acceptance mode will increasing accepting rate, however, it will reduce the security level of Bill Acceptor.

Note.4: Calibration card is needed.

Note.5: Decimal Point Position (DPP)= 2.

JPY 1000=1.00, JPY 2000=2.00, JPY 5000=5.00, JPY 10000=10.00

BR2300-JPY4 (MDB/ICT-BC/ccTalk)

Currency Assign Data

Interface Bill value	MDB	ICT-BC	ccTalk	Recycler banknote inventory	
BV1	JPY 1000	JPY 1000	JPY 1000	JPY 1000	40 pcs
BV2	JPY 2000	JPY 2000	JPY 2000	JPY 2000	40 pcs
BV3	JPY 5000	JPY 5000	JPY 5000	JPY 5000	40 pcs
BV4	JPY 10000	JPY 10000	JPY 10000	JPY 10000	40 pcs