

# L77F/PL77-KGS7

## L77F/PL77 Option Switch Settings : 1(Pulse/RS232 A0/ccNet/ICT104U)

Supported bill KGS 20, 50, 100, 200, 500, 1000, 5000 7bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / KGS 10	OFF	OFF	OFF							
2 Pulses / KGS 10	OFF	OFF	ON							
3 Pulses / KGS 10	OFF	ON	OFF							
4 Pulses / KGS 10	OFF	ON	ON							
5 Pulses / KGS 10	ON	OFF	OFF							
10 Pulses / KGS 10	ON	OFF	ON							
20 Pulses / KGS 10	ON	ON	OFF							
100 Pulses / KGS 10	ON	ON	ON							
Fast output Pulse <small>Lo= 50ms Hi=100ms</small>				ON						
★ Slow output Pulse <small>Lo= 50ms Hi=300ms</small>				OFF						
Inhibit level Active Low					ON					
★ Inhibit level Active High					OFF					
★ Accept KGS 20 & 50						ON				
Reject KGS 20 & 50						OFF				
★ Accept KGS 100 & 200							ON			
Reject KGS 100 & 200							OFF			
★ Accept KGS 500 & 1000								ON		
Reject KGS 500 & 1000								OFF		
★ Accept KGS 5000									ON	
Reject KGS 5000									OFF	
Simulation BillBox Has Been Removed										ON
★ Default										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip Switch 1 to 5 are only for Pulse mode.

# L77F/PL77-KGS7(Pulse/RS232 A0/ccNet/ICT104U)

## DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
RS232 A0 Mode		ON	ON	
★ Pulse Mode		ON	OFF	
ccNet Mode		OFF	OFF	
ICT104U Mode		OFF	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

## DIP SWITCHES SETTING : 2(ICT104U)

FUNCTION	SW1	SW2	SW3	SW4
Reserved	ON			
★ Reserved	OFF			
RS232 A0 Mode		ON	ON	
Pulse Mode		ON	OFF	
ccNet Mode		OFF	OFF	
★ ICT104U Mode		OFF	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

## DIP SWITCHES SETTING : 2(ccNet)

FUNCTION	SW1	SW2	SW3	SW4
Baud rate 19200	ON			
★ Baud rate 9600	OFF			
RS232 A0 Mode		ON	ON	
Pulse Mode		ON	OFF	
★ ccNet Mode		OFF	OFF	
ICT104U Mode		OFF	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

## Currency Assign Data

Interface Bill value	Pulse	RS232 A0	ccNet	ICT104U
BV1	KGS 20	KGS 20	KGS 20	KGS 20
BV2	KGS 50	KGS 50	KGS 50	KGS 50
BV3	KGS 100	KGS 100	KGS 100	KGS 100
BV4	KGS 200	KGS 200	KGS 200	KGS 200
BV5	KGS 500	KGS 500	KGS 500	KGS 500
BV6	KGS 1000	KGS 1000	KGS 1000	KGS 1000
BV7	KGS 5000	KGS 5000	KGS 5000	KGS 5000

## DIP SWITCHES SETTING : 2(RS232 A0)

FUNCTION	SW1	SW2	SW3	SW4
Reserved	ON			
★ Reserved	OFF			
★ RS232 A0 Mode		ON	ON	
Pulse Mode		ON	OFF	
ccNet Mode		OFF	OFF	
ICT104U Mode		OFF	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

## RS232 A0 INFORMATION

BillType Data	
Code	Denomination
1	Reserved
2	Reserved
3	KGS 20
4	KGS 50
5	KGS 100
6	KGS 200
7	KGS 500
8	KGS 1000
9	KGS 5000